

#### TECHNICAL DATA SHEET

#### DESCRIPTION

General purpose biaxially-oriented polypropylene (BOPP) film, reinforced with fiberglass, manufactured with pressure sensitive Acrylic adhesive.

Superior strength and bonds instantly when minimum pressure is applied. Ultra strong tensile strength and easy unwind ensure consistent, reliable seals to a variety of corrugated, plastics and metals.

#### PRODUCT APPLICATION

- Heavy weight box sealing
- Used for bundling and strapping, pipes, tubes, pallets, etc.
- Great temperature range and holding power

#### FEATURES

- Smooth, easy release from tape dispenser
- Ultra strong & durable polypropylene

#### FT-2580

Industrial Grade

<b>Adhesion to Steel</b> (ASTM 3330)	52 oz/in (59 N/100 mm)
<b>Tensile (Machine)</b> (ASTM D3759)	170 lbs
<b>Tensile (Cross)</b> (ASTM D3759)	N/A
<b>Elongation</b> (ASTM D3759)	7%
<b>Total Thickness</b>	6.00 mils (0.150 mm)
<b>Backing (BOPP)</b>	5.00 mils (0.125 mm)
<b>Adhesive</b>	Acrylic
<b>Application Range</b>	32 F to 120 F
<b>Colors</b>	Clear with Filament
<b>Sizes (Width)</b>	12 mm / 24mm / 48mm
<b>Sizes (Length)</b>	60 yards
<b>Storage</b>	40 F to 80 F 40% to 55% Humidity
<b>Shelf Life</b>	24 months

#### NOMINAL VALUES

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



*A Universal Company*

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030

www.incrediseal.com | sales@incrediseal.com

**Customer Service:** (410) 825-8300