

TECHNICAL SPECIFICATIONS

DESCRIPTION

Double sided repulpable tape provides a secure bond when the highest adhesion levels are required.

The tape is commonly used to for high temperature splicing applications in corrugated cardboard facilities and the paper industry. This product dissolves 100% in water for recycling applications.

PRODUCT APPLICATIONS

- Flying splices for paper applications and mills
- Great permanent bond holding power

FEATURES

- Smooth, easy release from hand rolls for easy application
- Ultra strong & durable

	5206	5208	5201
Peel Adhesion	10.0N/24mm	14.5N/24mm	17.5N/24mm
Static Shear (1000g)	10000 min		
Shear (180 degree)	21 lbs/24mm	26 lbs/24mm	31 lbs/24mm
Tape Color	Dark Blue	White	Light Blue
Total Thickness	2.50 mil	3.20 mil	4.40 mil
Adhesive	Water Soluble Acrylic		
Application Range	35°F to 95°F		
Operating Range	32°F to 392°F		
Sizes (Width)	3 mm to 1020 mm		
Sizes (Length)	60 yards, Custom Lengths		
Storage	40°F to 80°F 40% to 55% Humidity		
Shelf Life	12 months		
Repulpability	Adhesive (YES) Liner (YES)	Adhesive (YES) Liner (NO)	Adhesive (YES) Liner (NO)

NOMINAL VALUES

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



A Universal Company

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030

www.incrediseal.com | sales@incrediseal.com

Customer Service: (410) 825-8300