

TECHNICAL SPECIFICATIONS

DESCRIPTION

Single sided repulpable tape provides a secure bond when the highest adhesion levels are required.

The tape is commonly used to for high temperature splicing applications and roll starting when applied to cores and end tabbing

This product dissolves 100% in water for recycling applications.

PRODUCT APPLICATIONS

- Butt Splice, Overlap Splice for paper applications and mills
- Great bond holding power for core starting and end tabbing.

FEATURES

- Smooth, easy release from hand rolls for easy application
- Ultra strong & durable



5119

5122

Peel Adhesion	27.5N/24mm	27.5N/24mm
Tape Color	Kraft	White, Blue
Total Thickness	7.50 mil	8.60 mil
Tensile Strength	Machine 49 lb/ 25mm Cross 32 lb/ 25mm	Machine 41 lb/ 25mm Cross 36 lb/ 25mm
Tear Strength	Machine 27 lb/ 25mm Cross 20 lb/ 25mm	Machine 21 lb/ 25mm Cross 19 lb/ 25mm
Adhesive	Water Soluble Acrylic	
Application Range	35°F to 95°F	
Operating Range	32°F to 392°F	
Sizes (Width)	3 mm to 1040 mm, Custom Widths	
Sizes (Length)	60 yards, Custom Lengths	
Storage	40°F to 80°F 40% to 55% Humidity	
Shelf Life	12 months	
Repulpability	100%	

NOMINAL VALUES

All data are nominal values based on ASTM. This data may vary from roll to roll. The values below have been created using testing samples. We recommend the user test the product application, in their environment, to ensure 100% compliance.



A Universal Company

tenersen Lane Suite 4B | Hunt Valley, MD 21030
www.incrediseal.com | sales@incrediseal.com

Customer Service: (410) 825-8300